

Product Description

AT66 is a Plasticised PVC Protection Tape with a medium tack rubber adhesive.

Product Features

- A high grade and lightly plasticised polymeric PPVC backing for low stretch
- High performance cross-linked solvent based rubber-resin adhesive
- Excellent clean-remove characteristics
- Good thermal stability to 60° C
- Wide colour range— Black, White, Red, Green, Blue, Yellow, Orange & Service Green
- Supplied on a 3 Inch core in 33 metre lengths (Black also available in 66 metre)
- Can be written on with Texta pen



Benefits

- ✓ Highly flexible and conformable with easy unwind and tear
- ✓ Excellent UV and water resistance
- ✓ Non corrosive and long lasting adhesive system
- ✓ RoHS compliant

Key Markets

- Building and construction and, in particular, fabricators requiring a long-term protective medium for window and door frames
- Temporary lane marking for sports courts and factory demarcation
- Masking for sandblasting (can use multiple layers depending on grit pressure)
- Rural/agriculture and hydroponics
- Entertainment market—AV and lighting
- Colour coding

Applications

- Surface protection in the window frame industry (black), the product has an enviable reputation built over 30 years (G James Glass Testimonial –contact us for copy)
- Sport court marking (particularly temporary) and lane marking
- Colour coding components, intermediate stock and finished goods during manufacture
- Silage bag and pits for joining/patching/repair
- Sandblast masking for monumental masons
- Used as Console Tape on Audio Visual and sound mixing boards for marking levels

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.