



Product Type:	PVC Floor Marking Tape		
Colour:	White, Yellow, Orange Blue, Green, Red, Black Hazard Colours: Black/,Yellow, Red/White, Green/White		
Roll Size:	6mm to 1300mm in 33m Lengths		
Adhesive:	Rubber Natural		
Description:	A heavy duty plasticised PVC film, coated with a clear aggressive pressure sensitive adhesive.		
Application:	Factory demarcation areas, sports court markings. AT8S (Safety Tapes) helps employers meet their new statutory obligations under the Health and Safety at Work Act, i.e. first aid points, fire fighting equipment, hazardous areas.		
Technical Details:	Gauge:	0.14mm	
	Tensile Strength:	26 N/cm	
	Elongation at Break:	150%	
	Adhesion to Steel:	3.6 N/cm	
	Adhesion to Self:	2.5 N/cm	
	Water Extract:	pH	6.0 to 8.0
		Conductivity Max.	2.5 mS/m
	Service Temperature:	0°C to 60°C	
	Application Temperature:	5°C to 40°C	
Surface Preparation:	The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 30°C.		
Storage:	Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.		

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.