

Product Type: Conformable Heavy Duty Anti-slip Tape

Colour: Black, Yellow, Yellow/Black

Roll Size: 50mm and 150mm Widths in 20m Rolls
Other widths ex overseas available

Adhesive: Acrylic Solvent



Description: Aluminium foil backing with an Aluminium Oxide/Silicon Carbide – 36 Grit and coated with a solvent acrylic adhesive and PET Release Liner.

Application: For use on floors, stairways, ladders and gangways etc. to stop slipping, especially for escape/emergency exits and stairwells. The aluminium backing makes this grade particularly suitable for conforming to complex shapes e.g. checker plate.

Technical Details:

Gauge:	1.2mm (+/- 0.2mm)
Tensile Strength:	39 N/cm
Adhesion to Steel:	5.8 N/cm
Weight Per M ² :	1062g
Service Temperature	-5°C to 100°C
Storage Temperature	15°C to 25°C
Shelf Life:	12 Months

** Manufactured under ISO 9002/CNS 12682

Surface Preparation: The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

