

Product Type: Class 2 Reflective Hazard/Safety Warning Tape

Colour: Yellow/Black or Red/White Diagonal Stripe

Roll Size: Yellow/Black: 6mm to 1020mm in 10m
Red/White: 6mm to 450mm in 10m

Adhesive: Acrylic Solvent



Description: K9650 has backing of yellow/black stripe imprinted film, treated with reflective layer on one side, and coated with strong adhesion acrylic adhesive on the other side.

Application: This tape is the most suitable for hazard indication at construction field, inside warehouse, station or any worksite that is at dark places.

Technical Details:

Gauge:	0.14mm
Elongation at Break:	80%
Adhesion to Steel:	6.39 N/cm
Tensile Strength:	65.5 N/cm
Service Temperature:	-20°C to 60°C

Surface Preparation: Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. Freshly lacquered or painted surfaces should be completely cured. The compatibility of selected lacquers and paints should be tested by the user, prior to application of the material. For other applications the user is fully responsible for evaluating the suitability of the product, and for any risks associated with that use.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

