

Product Type:	Premium Double Sided Flatback Paper Tape		
Colour:	Beige		
Roll Size:	6mm to 1220mm in 33m Lengths		
Adhesive:	Rubber Natural		
Description:	A594 is a bleached flatback paper product coated with a high shear resistant pressure-sensitive natural rubber adhesive on both sides that bonds extremely well to almost any surface. The white easy release silicone kraft paper liner allows for either machine or hand application		
Application:	Golf grip replacement and repair, photograph mounting, carpet installation, textile manufacturing. Any application that requires two adhesive surfaces for joining.		
Technical Details:	Gauge:	0.178mm	
	Adhesion To Steel:	5.68 N/cm	
	Service Resistance:	Up to 93°C	
Surface Preparation:	The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 30°C.		
Storage:	Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.		

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.