

Product Type: High Specification Flame Retardant Cloth Tape

Colour: White (print "Advance AT2002")

Roll Size: 6mm to 1,200mm in 50m Length

Adhesive: Special F/R Solvent Free Rubber Resin

Description: Printed Polyethylene film laminated to an easy-tear cloth backing. Flexible with an aggressive flame retardant rubber resin adhesive system. The adhesive is non-corrosive and clean peels for up to 4 days at 50°C. Consistent unwind tension and good abrasion resistance. To FAR 25.853(a)

Application: Designed for applications where safety is paramount, building sites, shipyards and industrial facilities—including offshore platforms, mining and plant maintenance. Suitable for use on aircraft cargo containers. Used for a wide range of applications—sealing, joining, encapsulating etc.

Technical Details:	Gauge :	0.23mm
	Tensile Strength:	38 N/cm
	Elongation at Break:	45%
	Adhesion to Steel:	6.0 N/cm
	Service Temperature:	-10°C to 60°C
	Storage Temperature:	15°C to 25°C
	Shelf Life:	12 Months

Surface Preparation: The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

**DISCLAIMER:**

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.