

**Product Type:** PVC Medium Tack Protection Tape

**Colour:** Black, White, Yellow & Orange

**Roll Size:** Widths 6mm to 1250mm  
33m in Black, White & Yellow  
66m in Black & Orange



**Adhesive:** Rubber Natural

**Description:** A conformable building grade PVC tape with good tear and unwind characteristics for both hand and machine application. The special Rubber adhesive coating has low adhesion behaviour and strips cleanly and easily after application after significant periods of time. On basis of Third Party UV testing to ASTM G154 - 2012 (Lamp Type: UVB - 313, Lighting: 4huv/60°C, 0.71W/(m<sup>2</sup>·nm)@280 - 315nm, Condensation: 4huv/50°C, Exposure Time: 300h, 500h, 800h) Tenacious Tapes Guarantee performance for 6 months outdoors with an expectation of 12 months clean removal.

**Application:** Temporary indoor/outdoor protection of metal or hard wood surfaces during construction and painting/spraying work and polished metal surfaces during manufacturing processes.  
Note: This product is not recommended for use on freshly painted or coated surfaces.

**Technical Details:**

Gauge:	0.13mm
Tensile Strength:	20 N/cm
Elongation at Break:	130%
Adhesion to Steel:	0.60 N/cm
Moisture Vapour:	35-55g/m <sup>2</sup> per 24 hours
Service Temperature:	-5°C to 60°C

**Surface Preparation:** The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

**Storage:** Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

**DISCLAIMER:**

**Values:** All values presented have been determined by standard test methods and are average values only.

**Recommendations:** Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

**Warranty:** We can only warranty our products to the level that they are consistent with our Product Information Sheet values

**BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.**