

Product Type: Double Sided Butyl Tape

Colour: Black

Roll Size: 6mm to 1200mm in 30m Lengths

Adhesive: Butyl



Description: A high water-resistant butyl rubber adhesive coated on a polyethylene net to give it dimensional stability with a siliconized kraft paper release liner. The adhesive conforms to rough, textured surfaces and has a wide range of applications for joining, sealing waterproofing and vibration absorption. Butyl adhesives are useful for joining low energy surfaces such as PE.

Application:

- Fixing and sealing of joints for waterproofing in construction & civil eng.
- Joining and sealing of membranes
- Holding and sealing of sisalation in the HEVAC industry
- Mounting of light weight signage to textured surfaces e.g. rendered concrete
- Joining/mounting Corex/Corflute
- Vibration isolation of audio parts

Technical Details:

Gauge:	0.60mm
Tensile Strength:	27.0 N/cm
Adhesion to Steel:	9.8 N/cm
Service Temperature:	-30°C to 80°C
Storage Temperature:	15°C to 25°C
Shelf Life:	12 Months

Surface Preparation: The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

