

Product Type: FlexiFlash™ Sealing Tape

Colour: Clear/Translucent

Roll Size: 25mm to 930mm in 25m Lengths

Adhesive: Solventless Acrylic



Description: A special soft, clear flexible acrylic backing developed by Bow Tape to stretch and conform to complex surfaces. Coated with an extremely high tack solventless acrylic adhesive and supplied on a clear PET filmic release liner.

Application: Designed for sealing and weatherproofing of surfaces and often used as an over-seal of joints particularly in roofing applications. Whilst designed for external applications it can be painted over to improve both UV and aesthetic appearance. Commonly used over a rivetted surface in the transport industry where vibration and expansion and contraction can lead to metal fatigue and seals being potentially compromised. Suitable for repairing cracks in acrylic and glass fibre skylights. Excellent and versatile DIY repair for RV and marine applications.

Technical Details:

Gauge:	1.0mm +/- 10%
Tensile Strength:	15 N/cm
Elongation at Break:	350%
Adhesion to Steel:	40 N/cm
Service Temperature:	-20°C to 80°C (120°C Short Term)
Storage Temperature:	15°C to 25°C
Shelf Life:	12 Months

Surface Preparation: The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 25°C.

Storage: Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

