

Product Type:	Retro Reflective Tape Class 1—5 Year														
Colour:	White, Red, Yellow, Lime Yellow														
Roll Size:	24mm to 1,200mm in 20m & 5m Rolls														
Adhesive:	Acrylic Solvent														
Description:	A Class 1 prismatic grade retro reflective tape rated to 5 years outdoors in White, Yellow or Red. Coated with a high-grade solvent acrylic adhesive on a siliconized paper release liner.														
Application:	For signage and hazard warning at night. Used on vehicles and stationery equipment to improve visibility when operating under artificial light sources.														
Technical Details:	<table><tr><td>Gauge:</td><td>0.31mm</td></tr><tr><td>Tensile Strength:</td><td>23 N/cm</td></tr><tr><td>Adhesion to Steel:</td><td>10.9 N/cm</td></tr><tr><td>Service Temperature:</td><td>-40°C to 70°C</td></tr><tr><td>Storage Temperature:</td><td>15°C to 25°C</td></tr><tr><td>Service Life:</td><td>10 Years Indoors, 5 Years Outdoors</td></tr><tr><td>Shelf Life:</td><td>12 Months</td></tr></table>	Gauge:	0.31mm	Tensile Strength:	23 N/cm	Adhesion to Steel:	10.9 N/cm	Service Temperature:	-40°C to 70°C	Storage Temperature:	15°C to 25°C	Service Life:	10 Years Indoors, 5 Years Outdoors	Shelf Life:	12 Months
Gauge:	0.31mm														
Tensile Strength:	23 N/cm														
Adhesion to Steel:	10.9 N/cm														
Service Temperature:	-40°C to 70°C														
Storage Temperature:	15°C to 25°C														
Service Life:	10 Years Indoors, 5 Years Outdoors														
Shelf Life:	12 Months														
Surface Preparation:	The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 30°C.														
Storage:	Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.														

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.